



www.golnoor.com

Explosion Proof 



find us on QR code

Explosion Proof Catalogue
© Copyright Golnoor Co. All Right Reserved.


2023-1

golnoorclub



Explosion Proof

Linear Lighting Fixtures



ASTERIA lighting fixture, Golnoor series of flame proof light fittings, is the ideal solution for lighting in hazardous areas. This product benefits from a robust flameproof enclosure with the light transmitting part made of borosilicate glass and metallic part made of copper free aluminum covered with coatings making it suitable for use in corrosive, high temperature, and humid environments. The fixture is also suitable for outdoor applications due to its high degree of protection, IP67.

Maintenance is simplified due to gathering of all electrical components on a single frame moving on guides outwards thus eliminating the need for removal of the whole fixture for servicing. Through-wiring is included as the default feature which along with the movable frame helps to keep connected lightings turned on if one is out of service.

Brackets are available for ceiling, pole, and pendant mountings. Using the available auxiliary bracket along with main brackets facilitates and speeds up servicing. In case fixtures are used in locations with high risk of mechanical impacts an external protection and wire guard is available upon request.

Various electrical circuits meet the diverse need of lighting industry in hazardous areas. Fluorescent and LED light sources with various powers are supplied. Emergency models are provided to ensure lighting in case of power failures and sign models are available for lighting exit routes and identification of emergency exits.

ASTERIA

Explosion proof linear lighting fixtures
The ideal solution for lighting in hazardous areas


- Flameproof enclosure
- Zone 1, 2, 21, 22
- Degree of protection IP66/IP67
- LED/Fluorescent light source
- Normal/ Emergency/ Sign applications
- Through wiring
- Simplified maintenance

STANDARDS

For ASTERIA product family the following standards have been followed wherever applicable:

- IEC 60079-0
- IEC 60079-1
- IEC 60079-31
- IEC 60598-1
- IEC60598-2-22
- IEC 60529

FIXTURE SIZES




Dimensions (mm)

Size code	Dimensions (mm)			
	A	B	C	D
	1	140	148	1319
	2	140	148	709
	3	140	148	459

FLUORESCENT LUMINAIRES

Types: NF, EF




Technical data		
Type	NF	EF
Application	Normal	Emergency
Marking	II 2G Ex db IIC T6 Gb II 2D Ex tb IIIC T 85°C Db	II 2G Ex db IIC T6 Gb II 2D Ex tb IIIC T 85°C Db
EU-Type Examination Certificate	ECM 19 ATEX 5851 X	ECM 19 ATEX 5851 X
ATEX Certificate	ECM 22 ATEX-QS 5415	ECM 22 ATEX-QS 5415
Permissible ambient temperature	-20 °C to 55 °C	-20 °C to 40 °C
Degree of protection	IP66/IP67	IP66/IP67
Cable entries	2xM25 or 2xM20	2xM25 or 2xM20
Dimensions	Size1 ,2	See size1 ,2
Enclosure Color	RAL 7037	RAL 7037
Enclosure material	Copper free aluminum	Copper free aluminum
Protective cover	Borosilicate glass	Borosilicate glass
Type of mounting	Ceiling, Pendant, Pole	Ceiling, Pendant, Pole
Power factor	> 0.9	> 0.9
Voltage	230 V AC	230 V AC
Frequency	50/60 Hz	50/60 Hz
Circuit	Electronic ballast	Electronic ballast Emergency supply
Light source	2xT8, Fluorescent, 18/36W	2xT8, Fluorescent, 18/ 36W
Lamp cap	G13	G13
Connecting terminals	L,N,PE :6x2.5 mm2 True wiring	L,N,PE :2x2.5mm ²
Protection class	I	I
Emergency type	-	Maintained
Battery	-	4 Ah 3.6 V
Charging duration	-	24h
Rated operating duration	-	3h (one lamp)
Rated luminous flux	5000 lm/ 3000 lm	5000 lm/ 3000 lm

Type	Application	Content	Threads	Size	Order code
ASTERIA NF	Normal	2x Fluorescent lamp 36 W	2xM25	1	X10 NF 2360
ASTERIA NF	Normal	2x Fluorescent lamp 36 W	2xM20	1	X10 NF 2361
ASTERIA NF	Normal	2x Fluorescent lamp 18 W	2xM25	2	X10 NF 2180
ASTERIA NF	Normal	2x Fluorescent lamp 18 W	2xM20	2	X10 NF 2181

Type	Application	Content	Threads	Size	Order code
ASTERIA EF	Emergency	2x Fluorescent lamp 36 W	2xM25	1	X10 EF 2360
ASTERIA EF	Emergency	2x Fluorescent lamp 36 W	2xM20	1	X10 EF 2361
ASTERIA EF	Emergency	2x Fluorescent lamp 18 W	2xM25	2	X10 EF 2180
ASTERIA EF	Emergency	2x Fluorescent lamp 18 W	2xM20	2	X10 EF 2181

LED LUMINAIRES

Types: NL-LIOL




Technical data	
Type	NL-LIOL
Application	ACWL
Marking	II 2G Ex db IIC T6 Gb II 2D Ex tb IIIC T 85°C Db
EU-Type Examination Certificate	ECM 19 ATEX 5851 X
ATEX Certificate	ECM 22 ATEX-QS 5415
Permissible ambient temperature	-20 °C to 50 °C
Degree of protection	IP66/IP67
Cable entries	2xM25 or 2xM20
Dimensions	Size 3
Enclosure Color	RAL 7037
Enclosure material	Copper free aluminum
Protective cover	Borosilicate glass
Type of mounting	Ceiling, Pendant, Pole, Wall
Power factor	> 0.9
Voltage	230 V AC
Frequency	50-60 Hz
Illuminant	LED _s
Connecting terminals	L,N,PE : 6x2.5 mm ² True wiring
Protection class	I
Luminous intensity	>32.5 cd @25°

Type	Application	Threads	Color	Size	Order code
ASTERIA NL-LIOL	ACWL	2xM25	Red	3	X10 NL 115 100 LI
ASTERIA NL-LIOL	ACWL	2xM25	White	3	X10 NL 115 200 LI
ASTERIA NL-LIOL	ACWL	2xM20	Red	3	X10 NL 115 101 LI
ASTERIA NL-LIOL	ACWL	2xM20	White	3	X10 NL 115 201 LI

LED LUMINAIRES

Types: NL, EL



Technical data		
Type	NL	EL
Application	Normal	Emergency
Marking	II 2G Ex db op is IIC T6 Gb II 2D Ex tb op is IIIC T 85°C Db	II 2G Ex db op is IIC T6 Gb II 2D Ex tb op is IIIC T 85°C Db
EU-Type Examination Certificate	ECM 22 ATEX 5150 X	ECM 22 ATEX 5150 X
ATEX Certificate	ECM 22 ATEX-QS 5415	ECM 22 ATEX-QS 5415
Permissible ambient temperature	-20 °C to 55 °C	-20 °C to 40 °C
Degree of protection	IP66/IP67	IP66/IP67
Cable entries	2xM25 or 2xM20	2xM25 or 2xM20
Dimensions	Size 1, 2,3	Size 1, 2,3
Enclosure Color	RAL 7037	RAL 7037
Enclosure material	Copper free aluminum	Copper free aluminum
Protective cover	Borosilicate glass	Borosilicate glass
Type of mounting	Ceiling, Pendant, Pole, Wall	Ceiling, Pendant, Pole, Wall
Power factor	> 0.9	> 0.9
Voltage	230 V AC	230 V AC
Frequency	50-60 Hz	50-60 Hz
Illuminant	LEDs	LEDs
Connecting terminals	L,N,PE : 6x2.5 mm ² True wiring	L,N,PE : 6x2.5 mm ² True wiring
Protection class	I	I
Emergency type	-	Maintained
Battery	-	4 Ah, 4.8 V
Charging duration	-	24h
Rated operating duration	-	3h
Rated Luminous Flux	1800/2900/5200 lm	1800/2900/5200 lm

Type	Application	Content	Threads	Size	Order code
ASTERIA NL	Normal	144xLEDs, 40W	2xM25	1	X10 NL 1150 L
ASTERIA NL	Normal	144xLEDs, 40W	2xM20	1	X10 NL 1151 L
ASTERIA EL	Emergency	144xLEDs, 40W	2xM25	1	X10 EL 1150 L
ASTERIA EL	Emergency	144xLEDs, 40W	2xM20	1	X10 EL 1151 L

Type	Application	Content	Threads	Size	Order code
ASTERIA NL	Normal	72xLEDs, 20W	2xM25	2	X10 NL 1150 M
ASTERIA NL	Normal	72xLEDs, 20W	2xM20	2	X10 NL 1151 M
ASTERIA EL	Emergency	72xLEDs, 20W	2xM25	2	X10 EL 1150 M
ASTERIA EL	Emergency	72xLEDs, 20W	2xM20	2	X10 EL 1151 M

Type	Application	Content	Threads	Size	Order code
ASTERIA NL	Normal	15xLEDs, 15W	2xM25	3	X10 NL 1150
ASTERIA NL	Normal	15xLEDs, 15W	2xM20	3	X10 NL 1151
ASTERIA EL	Emergency / Sign	15xLEDs, 15W	2xM25	3	X10 EL 1150
ASTERIA EL	Emergency / Sign	15xLEDs, 15W	2xM20	3	X10 EL 1151

ACCESSORIES

EXTERNAL PROTECTIONS	ILLUSTRATION	TYPE	MATERIAL	NOTE	CODE
		External reflector	AISI304	Fixture Size 1	X10 R1
		External reflector	AISI304	Fixture Size 2	X10 R2
		External reflector	AISI304	Fixture Size 3	X10 R3
		Wire guard	AISI304	Fixture Size 1	X10 G1
		Wire guard	AISI304	Fixture Size 2	X10 G2
		Wire guard	AISI304	Fixture Size 3	X10 G3
		Round Wire Guard	AISI304	Fixture Size 1 Fixture Size 1 Fixture Size 1	X10 RG1 X10 RG2 X10 RG3

MOUNTING ACCESSORIES	ILLUSTRATION	TYPE	MATERIAL	NOTE	CODE
		Pole mounting	- AISI304 - Galvanized	- 2 pcs. With nuts, screws, washers - Available sizes: 1 1/2", 2"	X10 PM1.5 X10 PM2
		Ceiling mounting	- AISI304 - Galvanized	2 pcs. With nuts, screws, washers	X10 CM
		Suspended mounting	- AISI304 - Galvanized	2 pcs.	X10 SM
		Easy-maintenance	- AISI304 - Galvanized	Can be Used separately or along with other bracket types	X10 EM
		Wall mounting	- AISI304 - Galvanized	2 pcs. With nuts, screws, washers	X10 WM

PICTOGRAMS for EL type luminaires	ILLUSTRATION	TYPE	ORDER CODE
		Exit	X10 Exit
		Exit rout down	X10 DN
		Exit rout up	X10 UP
		Exit rout right	X10 RT
		Exit rout left	X10 LT
		Exit door right	X10 RD
		Exit door left	X10 LD
		Exit stairs right	X10 RS
		Exit stairs left	X10 LS

Explosion Proof
LED Floodlights Fixture



Atria has been developed as a new LED lighting fixture with the aim of redefining the concepts of compactness, versatility and ease of installation thanks to high intensity and efficiency LED plates. The Atria consists of a lighting fixtures size and represents the LED alternative for all those areas where it was normal to use lighting fixtures with discharge lamps. The body, made of aluminum alloy, is equipped with fins that act as a heat sink allowing a fast and effective dispersion of heat generated by the normal operation of the LED.

The geometric conformation of the cooling fins was also designed with the objective of minimizing the deposit of combustible dust, allowing the self-cleaning of the lighting fixture by air or water present in the environment. Furthermore, thanks to the absence of UV emission, there is no ionization of the air particles around the lighting fixture, an intrinsic characteristic of LED technology which limits the attraction of dust and insects. The design of the lamp body, in addition to being functional to the duration of the system, gives the equipment very high light efficiency. The electrical connection is easier thanks to a 'Ex e' terminal housing which allows the entry with a 'Ex e' cable gland (no barrier). In addition, an opposed plugged hole permits the through wiring connection.

ATRIA

LED lighting fixture

- Zone 1, 2, 21, 22
- Replaces traditional discharge lamps
 - Saves in energy, maintenance and installation costs
 - Instant, bright illumination
 - Suitable for GAS category IIC and IIB+H2

Connection


Direct connection to terminal board L, N, Pe.
Section 4mm² or 6mm²,

STANDARDS

CENELEC EN 60079-0: 2018, EN 60079-1: 2014, EN 60079-7: 2015, EN 60079-28: 2015,
EN 60079-31: 2014 and EUROPEAN DIRECTIVE 2014/34/UE

- . IEC 60079-0: 2017
- . IEC 60079-1: 2014
- . IEC 60079-28: 2015
- . IEC 60079-31: 2013
- . IEC 60079-7: 2015

FIXTURE SIZES



LED lighting fixture

Certification data		
Type	single 76 ~ 100 watt	twin 70/80/100 watt
Application	Normal	Normal
Marking	Ex II 2GD Ex de IIC T... Gb Ex tb IIIC T...°C Db IP66	Ex II 2GD Ex de IIC T... Gb Ex tb IIIC T...°C Db IP66
EU-Type Examination Certificate	ECM 23 ATEX *** X	ECM 23 ATEX *** X
ATEX Certificate	ECM 23 ATEX-QS ***	ECM 23 ATEX-QS ***
Permissible ambient temperature	-20 °C to 55 °C	-20 °C to 55 °C
Degree of protection	Ip66	Ip66
Cable entries	2xM25 or 2xM20	2xM25 or 2xM20
Dimensions	Ø 220x193mm	Ø 220x193mm
Enclosure Color	RAL 7037	RAL 7037
Enclosure material	Copper free aluminum	Copper free aluminum
Protective cover	Borosilicate glass	Borosilicate glass
Type of mounting	Ceiling, Pendant, Pole, Wall	Ceiling, Pendant, Pole, Wall
Power factor	>0.9	>0.9
Voltage	230 V AC	230 V AC
Frequency	50/60 Hz	50/60 Hz
Circuit	Electronic ballast	Electronic ballast

Photometric features	
LED Multichip	High power LED
Viewing angle	30-60-90°
Colour temperature	3000-4000-5000
CRI	>70
L70 B50	> 70000 h

Mechanical features	
Body	Low copper content aluminium alloy fitted with cooling fins for better heat dissipation
Glass face	Shock and temperature resistant tempered glass sealed with aluminium ring
Gaskets	Acid, hydrocarbon and high temperature resistant silicone
Supporting bracket	Stainless steel AISI304/ 316L
Bolts and screws	Stainless steel
Entries	2 x ISO M20 entries OR 3x ISO M20
Coating	coating Ral 7037(grey)

Selection		
Type	100 W	twin 200 W
Temp	class/max surface temp	class/max surface temp
temperature class	T4 / 135 °C	T4 / 135 °C
	T5 N/A	T5 N/A
	T6 N/A	T6 N/A
Lumen	12000 lm	24000 lm
Efficiency	120 lm/W	120 lm/W
Weight	8 kg	16 kg
Size	250x250x170 mm	250x250x170 mm
Order code	ATR00100-00	ATR00200-00

ACCESSORIES AVAILABLE / SPECIAL REQUESTS

Additional cable gland for unarmoured cable

MOUNTING ACCESSORIES		Supporting bracket	wall or structure mounting OR ceiling mounting	Material: stainless steel AISI 316L/304

Photometric diagram(polar curve)
On golnoor web site you can download .LDT lighting data files for the design and simulation of lighting levels , rendering and ray tracing.



Explosion Proof

GJB: Golnoor junction box



Serie GJB Explosion-proof boxes made of copper free Aluminum varies from terminal boxes to enclosures. They are equipped with pillar or strip terminals and assembly plate to distribute electricity in hazardous areas including zone 21,2,1 and 22. In addition, big sizes can be equipped with circuit breakers but without external access as a control panel to be able to and the fault more easily.

Cables enter to GJBs via explosion protected conduits or cable glands and unused drilled holes would be closed with protected stopping plugs. They can provide optional external earth connection and high IP protection degree.



Ex-d Light Alloy Boxes	
Marking acc. To 2014/34/EU	Ex II 2 G Ex db IIC T4/T5/T6 Gb Ex II 2 D Ex tb IIIC T85 C / T100 C Db
Applicable Zones	1, 2 - 21, 22
EU-Type Examination Certificate	ECM 18 ATEX 2444 X
ATEX Certificate	ECM 22 ATEX-QS 5415
Permissible ambient temperature	-20°C to +55°C
Rated Voltage	690 V
Degree of Protection acc. to EN60529	IP66/IP67
Enclosure Material	Copper-free Aluminum
Enclosure Color	GJB1,2,3,4,5 : Painted - Ral Color : 7072

Ordering Details					
Type	Power Dissipation (w)			Rated Current (A)	Weight (kg)
	T6	T5	T4		
GJB1	8	14	28	40	1
GJB2	16	21	42	61	2
GJB3	30	36	56	60	3.5
GJB4	57	68	125	150	7.5
GJB5	82	121	246	250	17.5




Max. No. of Terminals										
Terminals	2.5	4	6	10	16	25	35	50	70	95
GJB1	8	7	-	-	-	-	-	-	-	-
GJB2	13	12	10	8	-	-	-	-	-	-
GJB3	15	14	12	10	8	-	-	-	-	-
GJB4	22	20	16	13	11	9	8	6	6	-
GJB5	1x42	1x38	1x30	1x25	1x20	1x18	1x15	1x12	1x10	1x6
	2x40	2x35	2x25	2x20	2x15	2x12	2x10	-	-	-


Max. Metric Entries Per Side							
Type	M20	M25	M32	M40	M50	M63	M75
GJB1	1	1	-	-	-	-	-
GJB2	3	2	1	-	-	-	-
GJB3	4	2	2	1	1	-	-
GJB4	5	4	2	2	1	1	-
GJB5	8	6	4	3	3	2	1

Max. NPT Entries Per Side							
Type	$\frac{1}{2}$ "	$\frac{3}{4}$ "	1"	$1\frac{1}{4}$ "	$1\frac{1}{2}$ "	2"	$2\frac{1}{2}$ "
GJB1	1	1	-	-	-	-	-
GJB2	3	2	1	-	-	-	-
GJB3	4	3	2	2	2	-	-
GJB4	6	5	3	2	2	1	-
GJB5	10	8	5	3	3	2	1


Due to different important parameters, please consult with the technical department to choose suitable junction boxes. These tables are just for information.




GJB1



GJB2



GJB 3,4,5




Type	External			Internal		Mounting	
	A	B	C	F	C'	D	E
GJB1	110	110	95	Ø84	57	115	6.5
GJB2	150	152	110	Ø122	73	162	9
GJB3	169	169	125	□137	76	235	7.5
GJB4	221	221	195	Ø174	142	248	11
GJB5	337	337	187	Ø297	110	375	11

All dimensions are in millimeters with tolerance.


Explosion Proof

GLCS: Golnoor Local Control Station




Several series of flameproof control units are available for the operation and monitoring of circuits and machinery in harsh or hazardous environments. The GLCS series is Ex d IIC certified and can hold up to four operators. Multiple control functions are available such as push buttons, LED status indicators, and control switches. The control units are manufactured from copper-free aluminum, which provides optimal protection from most environmental hazards.

Technical Data



GLCS 1



GLCS 3

Ex-d Light Alloy Boxes

Marking acc. To 2014/34/EU	Ex II 2G Ex db IIC T6 Gb Ex II 2D Ex tb IIIC T85°C Db
Applicable Zones	1, 2 - 21, 22
EU-Type Examination Certificate	ECM 23 ATEX **** X
ATEX Certificate	ECM 23 ATEX-QS ****
Permissible ambient temperature	-20°C to +55°C
Rated Voltage	600 V
Degree of Protection acc. to EN60529	IP66/IP67
Enclosure Material	Copper-free Aluminum
Enclosure Color	Painted- Ral color: 7072




Ordering Details

Type	Rate Current (A)	Max.Dissipated Power (W)	Max.Weight (kg)	Max.No. Actuators
GLCS1	40	10	2.2	1
GLCS3	60	30	6	3-4*

Max. No. Metric Entries per side

Type	M20	M25	M32	M40	M50
GLCS1	1	1	-	-	-
GLCS3	4	2	2	1	1

Actuators

Pushbutton (Start/stop)	Mushroom head emergency button (Push/Pull)	Selector switch
		

* 4 actuators may only be used in special circumstances (power dissipation, operation terms, etc)

Pushbutton (Start/Stop)

Bushing	Nickel-plated brass
Internal shaft	Stainless steel
Gasket	Compressed asbestos fiber
Internal O-ring	EPDM
Device mounting	Screws into the lid (M30x2)
Sticker	Colored PMMA (green, red, ...)
Contact	Schneider ZB2 (NO/NC)
Rated voltage	600V based on Schneider's catalog
Rated current	10A based on Schneider's catalog
AC15 Ue/Ie	240V/3A based on Schneider's catalog
DC13 Ue/Ie	250V/0.27A based on Schneider's catalog
Rated thermal current	I _{th} = 10A
Contact operation	Slow break, spring return


Mushroom head emergency button

Bushing	Nickel-plated brass
Internal shaft	Stainless steel
Gasket	Compressed asbestos fiber
Internal O-ring	EPDM
Device mounting	Screws into the lid (M30x2)
Sticker	Colored PMMA (green, red, ...)
Contact	Schneider ZB2 (NO/NC)
Rated voltage	600V based on Schneider's catalog
Rated current	10A based on Schneider's catalog
AC15 Ue/Ie	240V/3A based on Schneider's catalog
DC13 Ue/Ie	250V/0.27A based on Schneider's catalog
Rated thermal current	I _{th} = 10A
Contact operation	Slow break, spring return
Actuator operation	Push/pull (pull to release)

Selector switch

Bushing	Nickel-plated brass
Internal shaft	Stainless steel
Gasket	Compressed asbestos fiber
Internal O-ring	EPDM
Device mounting	Screws into the lid (M30x2)
Handle	ABS
Selector	TRS (GL model) - 1/2/3 phase
Rated voltage	690V

Dimension Details



Item	Illustration	Switching Diagram	Description	Color
1			mushroom button Latching, Pull to Release 1*NO/1*NC 250V 3 A	Red
2			12/16 A	Black/Ni Plated
3			Start+Stop Push Button 1*NO/1*NC 250V 3 A	Red
				Green
4			Stop Push Button 1*NC + Start Push Button 1*NO 250V 3 A	Red + Green
5			Start+Stop Push Button 1*NO/1*NC 250V 3 A mushroom button Latching, Pull to Release 1*NO/1*NC 250V 3 A	Green + Red
6			Start+Stop Push Button 1*NO/1*NC 250V 3 A + Start+Stop Push Button 1*NO/1*NC 250V 3 A + mushroom button Latching, Pull to Release 1*NO/1*NC 250V 3 A	Red + Green + Red
7		Tailor-made solution	On request	On request
8		Tailor-made solution	On request	On request

Explosion Proof

GJBF: Golnoor Junction Box Flange Type



GJBF series of Ex d IIB+H₂ certified enclosures forms the optimal basis for the application-specific configuration of terminal boxes, control stations, and control and distribution panels. A wide range of components and control functions can be integrated into one of many Ex d and Ex tb certified flameproof enclosures. They come in many sizes and designs and are manufactured from copper-free aluminum with increased corrosion resistance. The durable, versatile enclosures meet the requirements of many industries, including offshore and marine applications. A choice of windows allows viewing of integrated monitoring functions. Electrical components can be integrated as per customer specification.


GJBF

- 14 different sizes
- copper-free aluminum junction boxes
- Gasket resistant to acids and high temperatures
- IK10 mechanical strength
- IP66/67
- Earth bolt

Selection

Marking of product	Ex II 2G Ex db IIB+H2 T6, T5, T4 Gb Ex II 2D Ex tb IIIC T85°C, T100°C, T135°C Db
EU-Type Examination Certificate	ECM 23 ATEX ****X
ATEX Certificate	ECM 23 ATEX-QS ****
Application	Terminal box or Local control panel
Material	copper-free aluminum
Finish	coated or painted to suit customer application
Ingress protection	IP 66/67 to IEC 60529
Ambient temperature	-30°C to +55°C
Lid fixing	Metric socket head stainless steel screws
Earthing	Metric Internal / External screws
Enclosure mounting	2 fixing brackets
Drain plug	customer application
Entries	through walls
Bolts and screws	Stainless steel captive variety
Mounting	AISI 304 Stainless steel feet with Stainless steel screws
Rail	Reed mounting rail (All steel versions are electroplated and additionally coated with a white chromate)
Rated voltage	1000 Vac/dc
Rated current	1000 A
Rated frequency	50/60 Hz


Junction box and Local control panel				
Product type	Dimension and Tolerance (±5)			Max. Power Dissipation at +40°C, for T4 Without Indicator Light (W)
	A	B	C(C'=optional)	
GJBF1	290	220	180(200)	130(135)
GJBF2	390	290	240(270)	235(240)
GJBF3	470	350	240(280)	345(360)
GJBF4	580	430	250(290)	480(540)
GJBF5	680	510	350(380)	730(745)
GJBF6	750	560	350(400)	840(880)
GJBF7	870	650	420(480)	1550(1740)



D Thread diameter	1	2	3	4	5	6	7	8
ISO 261/965	20x1.5	25x1.5	32x1.5	40x1.51	50x1.51	63x1.5	75x1.52	90x1.5
ISO 7-1/ 228	1/2 "	3/4 "	1"	1/4 "	1/2 "	2 "	1/2 "	3 "

Hole drilling in body																
Side	Side A								Side B							
Thread diameter	1	2	3	4	5	6	7	8	1	2	3	4	5	6	7	8
Product type	Maximum Quantity Per Hole Type								Maximum Quantity Per Hole Type							
GJBF1	8	7	5	3	2	2	2	1	6	4	2	2	2	1	1	-
GJBF2	21	14	10	8	7	3	3	2	12	11	6	6	3	2	2	1
GJBF3	24	20	12	10	9	4	3	2	18	14	8	7	5	3	2	1
GJBF4	30	18	16	14	11	5	5	3	21	17	11	10	8	5	3	2
GJBF5	40	36	24	21	14	12	10	4	35	24	18	15	11	8	6	2
GJBF6	44	42	30	23	15	12	11	4	36	30	21	17	10	8	7	3
GJBF7	81	65	44	40	27	21	17	6	55	50	32	28	18	15	14	5

The number of entries indicated above is for reference only, and may vary depend on application requirement e.g.: type of cable entries, number of terminals, ...




Product type	TERMINAL CROSS-SECTIONAL AREA										
	2.5	4	6	10	16	25	35	50	70	95	150
GJBF1	1x22	1x20	1x17	1x14	1x11	1x10	1x8	1x7	1x3	-	-
GJBF2	2x36	2x33	2x27	2x22	2x17	2x16	1x13	1x11	1x6	1x6	1x4
GJBF3	3x50	3x46	3x38	3x30	3x24	3x22	2x18	1x15	1x13	1x8	1x6
GJBF4	3x70	3x64	3x52	3x42	3x33	3x30	2x25	1x21	1x19	1x10	1x10
GJBF5	3x78	3x72	3x58	3x47	3x37	3x34	2x28	1x23	1x21	1x12	1x10
GJBF6	4x87	4x80	4x65	4x52	4x42	4x38	3x32	2x26	1x25	1x19	1x12
GJBF7	4x105	4x96	4x78	4x63	4x50	4x46	3x38	2x31	1x30	1x20	1x15

The maximum number of standard terminals refers to RAAD terminals. The number of terminals indicated above is for reference only, and may change depend on application requirement and heat dissipation.

Thread Chart									
ISO 261/965	M16	M20	M25	M30	M35	M40	M42	M35	
ISO 7-1/ 228	3/8 "	1/2 "	3/4 "	1"	-	-	-	-	


Window type	Windows Dimensions
	Thread
Window1	M90x2
Window2	M133x2
Window3	M196x2

Product type	Max Hole Drilling QTY in Door	
	with more Thickness	with Stiffener
GJBF1	6	6
GJBF2	12	8
GJBF3	15	8
GJBF4	24	9
GJBF5	35	12
GJBF6	48	16
GJBF7	63	20



Explosion Proof

GSB: Golnoor Junction Box
Stainless steel Type



GSB series is a range of terminal boxes that can be equipped with a variety of terminals and cable glands. The enclosures are manufactured from electropolished AISI 304 stainless steel to provide excellent tarnish and corrosion resistance. This surface finish is designed to meet hygienic requirements valid in pharmaceutical and food processing plants. All GSB enclosures feature a sealing method which prevents accumulated dirt, dust, and moisture from entering the enclosure when the hinged lid is opened.

Durable materials allow the terminal box to be used in ambient temperatures between -30°C and 55°C / -20°C and 40°C. For terminal and cable gland configuration options.

GSB

- 7 different sizes
- 304/316 L stainless steel junction boxes
- Gasket resistant to acids and high temperatures
- IK10 mechanical strength
- IP66/67
- Earth bolt

Ex-e Stainless Steel boxes

Marking of product	Ex II 2G Ex eb IIC T6 Gb Ex II 2D Ex tb IIIC T85°C Db
Applicable Zones	1,2 - 21, 22
EU-Type Examination Certificate	ECM 23 ATEX ****X
ATEX Certificate	ECM 23 ATEX-QS ****
Application	Terminal box or marshaling box
Material	Stainless steel
Finish	Stainless steel may coated or painted to suit customer application
Ingress protection	IP 66 to IEC 60529
Ambient temperature	-30°C to 55°C / -20°C to 40°C
Lid fixing	4 or more M6 stainless steel screws
Earting	M5 Internal /M8 External stainless steel screws
Enclosure mounting	2 or 4 slotted fixing brackets for M8/M10 screws
Drain plug	customer application
Entries	through walls
Bolts and screws	Stainless steel captive variety
Mounting	Welded AISI 304 Stainless steel feet
Rail	Reed mounting rail (All steel versions are electroplated and additionally coated with a white chromate)
Rated voltage	1000 Vac/dc
Rated current	312 A
Rated frequency	50/60 Hz

Body Drilling Data

D Thread diameter	1	2	3	4	5	6	7	8
ISO 261/965	20x1.5	25x1.5	32x1.5	40x1.5	50x1.5	63x1.5	75x1.5	90x1.5
Through hole	Ø20.2	Ø25.2	Ø32.2	Ø40.2	Ø50.2	Ø63.2	Ø75.2	Ø90.2

Hole drilling in body

	Side A					Side B				
	20	25	32	40	50	20	25	32	40	50
GSB1	4	2	1	-	-	4	2	1	-	-
GSB2	5	2	1	-	-	3	2	1	-	-
GSB3	14	12	5	4	3	14	12	5	4	3
GSB4	16	12	5	5	4	14	12	5	4	3
GSB5	18	14	6	5	5	12	10	4	3	3
GSB6	18	14	6	5	5	18	14	6	5	5
GSB7	20	16	7	6	5	16	12	5	5	4

The number of entries indicated above is for reference only, and may vary depend on application requirement e.g.: type of cable entries, number of terminals,...



Max. No. of Terminals

Terminals	2.5	4	6	10	16	25	35	50	70
GSB1	9	-	-	-	-	-	-	-	-
GSB2	16	13	10	-	-	-	-	-	-
GSB3	2x27	2x25	2x20	2x16	2x12	2x11	-	-	-
GSB4	2x31	2x29	2x22	2x17	2x13	2x12	2x8	7	-
GSB5	2x45	2x36	2x29	2x22	2x18	14	13	11	-
GSB6	3x39	3x34	3x27	3x21	3x16	3x14	3x12	3x8	-
GSB7	3x37	3x34	3x27	3x22	3x16	3x15	3x12	3x9	3x8

Dimension Details

Code	Outside dimensions A x B x C (C'=optional)	Inside dimensions	mounting	
		- - -	A1	B1
GSB1	170x170x100	165x165x85	70	204
GSB2	220x150x100 (130)	215x145x85	120	182
GSB3	300x300x150 (215 or 315)	295x295x135	200	332
GSB4	350x300x200 (215 or 315)	345x295x185	250	332
GSB5	400x280x200 (215 or 315)	395x275x185	300	312
GSB6	400x400x200 (215 or 315)	385x395x185	300	432
GSB7	450x350x200 (215 or 315)	445x345x185	350	382

Dimension Details



Explosion Proof Cable Gland



Golnoor introduces a solution for every cable type used in industrial and hazardous areas- onshore and offshore, under and above ground. Golnoor cable glands, thread conversions, and installation accessories are designed to adhere to global specifications of IEC wiring standards and meet international certification requirements constituting IEC and ATEX certifications for gas and dust applications. Our manufacturing facilities are the most productive and safest solution to fulfill your need in the closest way to your demand. Furthermore, our technical teams are ready to be on your side in training, commissioning and installation stage.

Specifications

Material

Metallic- Nickel plated brass

Nickel-plated brass provides superb protection against corrosion and contamination under severe conditions in extreme environments and in this regard, it is the most appropriate material for oil and gas and petrochemical industries and refineries.

All internal and external components emerge electroplating process by the thickness of 5 to 10 microns and uniform coating is assured under the quality control procedure.

Seal- Silicone

Silicone is opted as seal material to provide a wide range of thermal performance in extreme conditions.


Operating temperature range

Silicone seals operates in temperature conditions varied from -30 to +140° C.

Clamping


Outer sheath cable sealing

The outer seal is designed in the respect of ensuring cable sealing and ingress protection. (Fig 1)



Inner sheath cable sealing


The inner seal is figured to work same tasks as outer seal in addition to satisfy flame-path protection commitments. (Fig 2)



Armored cable clamping


The designation complies clamping of all types of armored cables include

- Steel wire armored/ single wire armored (SWA) cable
- Steel tape armored (STA) cable
- Braided marine shipboard cable
- Lead sheath armored cable
- Type P cable (Fig 3).



Ingress protection- IP


Exploiting thread to thread engagement prepare IP66. For more protection up to IP68, additional sealing or gasket could be used.



XCGNA- for non-armored cable




Technical Specification	
Suited for cables	Non-armored/ marine shipboard/ Type P/ Tray cables
Permissible zones	Group IIA, IIB, IIC, zones 1, 2, 21, 22
Marking acc. To 2014/34/EU	Ⓢ II 2G Ex db IIC Gb/ II 2G Ex eb IIC Gb/ II 3G Ex nR IIC Gc Ⓢ II 2D Ex tb IIIC Db
EU-Type Examination Certificate	ECM 19 ATEX 5727 X
ATEX Certificate	ECM 19 ATEX-QS 6210
Permissible ambient temperature	-30°C to +140°C
Degree of Protection acc. to EN60529	IP66- IP68 with gasket
Material	Nickel-Plated Brass
Seal	Silicone
Accessories (Kit)	Locknut to secure gland body Earth tag to provide earth continuity Shroud to protect gland body



Series	ISO thread size	Outer sheath Min-Max	A _{max}	B _{max}	L _{max}	Catalog number
XCGNA	M20S x1.5	7.0 -12.0	24	22	43.7	XCGNAM20S
XCGNA	M20L x1.5	10.0 -15.5	26	24	46.8	XCGNAM20L
XCGNA	M25 x1.5	13.5 -20.5	33	30	51.6	XCGNAM25
XCGNA	M32 x1.5	18.0 -27.0	45	41	61.0	XCGNAM32
XCGNA	M40 x1.5	23.0 -34.0	53	48	64.4	XCGNAM40
XCGNA	M50 x1.5	35.0 -47.5	69	64	72.8	XCGNAM50
XCGNA	M63 x1.5	42.0-56.0	82	75	76.3	XCGNAM63
XCGNA	M75 x1.5	50.0-64.5	93	85	86	XCGNAM75

All dimensions are in millimeters with tolerance.



XCGA- for armored cable

Technical Specification	
Suited for cables	SWA/ SWB/ STA/ Braided marine shipboard/ Type P/ Lead sheathed cables
Permissible zones	Group IIA, IIB, IIC, zones 1, 2, 21, 22
Marking acc. To 2014/34/EU	Ⓢ II 2G Ex db IIC Gb/ II 2G Ex eb IIC Gb/ II 3G Ex nR IIC Gc Ⓢ II 2D Ex tb IIIC Db
EU-Type Examination Certificate	ECM 19 ATEX 5727 X
ATEX Certificate	ECM 19 ATEX-QS 6210
Permissible ambient temperature	-30°C to +140°C
Degree of Protection acc. to EN60529	IP66- IP68 with gasket
Material	Nickel-Plated Brass
Seal	Silicone
Accessories (Kit)	Locknut to secure gland body Earth tag to provide earth continuity Shroud to protect gland body

Series	ISO thread size	Inner sheath Min-Max	Outer sheath Min-Max	Armor Min-Max	A _{max}	B _{max}	L _{max}	Catalog number
XCGA	M20S x1.5	7.0 -12.0	10.0 -15.5	0.2 -1.3	26.5	24	65.7	XCGAM20S
XCGA	M20L x1.5	10.0 -15.5	13.5 -20.5	0.2 -1.3	33	30	73.7	XCGAM20L
XCGA	M25 x1.5	13.5 -20.5	18.0 -27.0	0.2 -1.6	45	41	85.7	XCGAM25
XCGA	M32 x1.5	18.0 -27.0	23.0 -34.0	0.2 -1.6	53	48	93.5	XCGAM32
XCGA	M40 x1.5	23.0 -34.0	29.0 -40.5	0.2 -2.0	60.5	55	99.8	XCGAM40
XCGA	M50 x1.5	29.0 -40.5	35.0 -47.5	0.2 -2.5	69	64	108.5	XCGAM50
XCGA	M63 x1.5	35.0-47.5	42.0-56.0	0.2 -2.5	82	75	111.5	XCGAM63
XCGA	M75 x1.5	42.0-56.0	50.0-64.5	0.2 -2.5	92	85	123.6	XCGAM75

All dimensions are in millimeters with tolerance.



XSP- stopping plug

Technical Specification	
Permissible zones	Group IIA, IIB, IIC, zones 1, 2, 21, 22
Marking acc. To 2014/34/EU	Ⓔ II 2G Ex db IIC Gb/ II 2G Ex eb IIC Gb Ⓔ II 2D Ex tb IIIC Db
EU-Type Examination Certificate	ECM 19 ATEX 5779 U
ATEX Certificate	ECM 19 ATEX-QS 6210
Degree of Protection acc. to EN60529	IP66- IP68 with gasket
Material	Nickel-Plated Brass

Series	ISO thread size	Thread height	Catalog number
XSP	M20	15.0	XSPM20
XSP	M25	17.0	XSPM25
XSP	M32	15.0	XSPM32
XSP	M40	15.0	XSPM40
XSP	M50	15.0	XSPM50
XSP	M63	15.0	XSPM63
XSP	M75	15.0	XSPM75

All dimensions are in millimeters with tolerance.



XAR- adaptor-reducer

Technical Specification	
Permissible zones	Group Group IIA, IIB, IIC, zones 1, 2, 21, 22
Marking acc. To 2014/34/EU	Ⓔ II 2G Ex db IIC Gb/ II 2G Ex eb IIC Gb Ⓔ II 2D Ex tb IIIC Db
EU-Type Examination Certificate	ECM 19 ATEX 5779 U
ATEX Certificate	ECM 19 ATEX-QS 6210
Degree of Protection acc. to EN60529	IP66- IP68 with gasket
Material	Nickel-Plated Brass

	Female						
Male	M20	M25	M32	M40	M50	M63	M75
M20		XARM20-M25	XARM20-M32				
M25	XARM25-M20		XARM25-M32	XARM25-M40			
M32	XARM32-M20	XARM32-M25		XARM32-M40	XARM32-M50		
M40		XARM40-M25	XARM40-M32		XARM40-M50		
M50			XARM50-M32	XARM50-M40		XARM50-63	
M63					XARM63-50		XARM63-M75
M75						XARM75-63	

All dimensions are in millimeters with tolerance.

